	• •						•				•	• •		• •		•	•	•					•	•	
														• •											 ÷ +
	DR	N כ	TRL																						
	[5 T A	GE	V]																						
	DOR/																								
	1JUR/ 70 8																								
	/U C	ין טנ "				. [Ê.										. (
							F				_'_							The second							
								X DA	5					-	Y		13								
			. 6	6	5				0	19	-		-						1000		3-				
			-	1								6	R		2 1						C				
										1			1	1						ų					
							. 6							Y		. 1	R								
		_				_					-	T	3		/ 					_	_	_	_		
															1	20									
							Co			0					00		(HO)								
							Non			1	SF						L.								
												*	*								-		-		
1							1		뫑			(5555													
					-			7				SAN					In:				1				
					1									\odot				-		$\sum_{i=1}^{n}$	-		-		
1									4-4							-			1						
												-	1/						1		1				
	• •											1	10 :	0		*									
	• •		-		5		1			-11-	- in	िन्द		1 500					1						
	• •					V	/	-	/1		a lat			55 - KORTES+)		NUC ^{a e}			1				•		
	• •		-						-	-	- 04	7 6			- []	Ň.			1				-	•	
	• •						/								- [- 6	R		1	-					
	• •			• •				-	•						•	- 6				-					
	• •		-].	-							- [-		-			
	• •		•		-				-			• •		• •		•	•	•		-				•	
	• •		-		-	•	•	• •						• •				-							
		DE	ŇΑ	ME	1 -	-		• •						÷ 1			•	-					-	•	
	-			1		-		-		-								-							
			-		\prec	E						N		TI	ΙE	20									
			1				•										1	-	· •			>		\checkmark	
	• •													• •					· •			59			
	• •													• •	н		•						Ŭ/		
	• •													• •	н		•								
•	[D1	ST	NG	uis	HIN	١G	FE	ATL	J R E	S]		• •		•											
	NA	TU	RA	LLY	ΎΑ	W	N	NER	2			•	-								ſ			•	
							•					• •		• •			•								
	• •						1					•		•					-						
	• •							• •				• •		•			•			-					

DRDNTRL

20155

NATURALLY A WINNER.

As simple to use as it is rich in technological content, the SAME Dorado Natural stands out for its great versatility too, working in the best possible way both in the open field and in limited spaces (i.e. greenhouses, stables).

The new FARMotion 35 engines, together with optimum comfort and a wide choice of configurations are characteristics that make the SAME Dorado Natural the ideal tractor for winning every match. The new cab provides a modern, comfortable and ergonomic work environment, and the new transmissions not only ensure the right pace out in the field but are also designed to travel at 40 km/h on the road with the engine running in economy mode. The SAME Dorado Natural range offers models that boast excellent manoeuvrability, to move easily in even the narrowest spaces, and a torque supply that's ideal for the agricultural context. At the same time, the tried and tested 5-speed transmissions - completed with modern electro hydraulic engagement for front wheel drive and differential locking guarantee excellent traction and robustness, allowing even the hardest field work to be easily carried out.



DRDNTRL

An engine conceived for farming. In day to day use, the difference this makes is clear!

AGRIEL

IGIN

The Dorado Natural range comprises 4 models from 66 to 102 HP, powered by advanced 3-cylinder FARMotion 35 engines that not only offer compactness and proven reliability but also efficiency minimal maintenance and needs. The innovative FARMotion 35 engine is purposely designed," in fact," for agricultural use; the 3-cylinder version is fitted on the SAME Dorado Natural, to enhance the already excellent handling of these machines. The use of a viscostatic fan, turbocharger with intercooler and waste-gate valve, along with a common rail injection system up to 2,000 bar and the latest 7-hole piezoelectric injectors (for optimum diesel sprauing to ensure efficient combustion), produces first class results whilst at the same time keeping diesel consumption at the lowest levels in this category. Furthermore, the FARMotion



35 engines offer almost constant power supply over a wide speed range and with high torque, even at low rotation speeds. The advanced conception and innovative technical solutions ensure that FARMotion 35 engines comply with the limits envisaged by Stage V in terms of polluting emissions, merely using the DOC+DPF (for the models 70 and 80) or DOC+DPF+SCR (for the models 90-100). FARMotion 35 engines are distinguished by their outstanding maximum performance figures: the rotation speed is only 2,200 rpm; the version installed on the SAME Dorado 100 Natural provides a torque reserve of 35% and it develops a maximum torque of 417 Nm. Apart from optimising consumption, the fully electronic diesel injection control also allows two work speeds to be memorised. These are directly activated from the driver's seat by means of a dedicated button command, leaving the ECU with the task of proportioning fuel use on the basis of the load. This means the connected attachments can be used in a smooth manner, even with the sudden load variations that are a typical feature of many types of agricultural work. The new layout underneath the bonnet offers a sheltered, protected area for both the DOC catalytic converter and the new PowerCore 2-stage air filter which can be fitted upon request with a dust ejector). Two practical sliding screens have been added, to protect the radiator pack and facilitate maintenance.

. 70 :	.66 HP	/ "48,9 kW
· 80 :	. 76 HP	/ .55,8 kW .
·90:	• 9) HP	/ =67=kW =
100:	102 HP	/ =75=kW =

•

ENGINE

RANSMISSION, TO AND HYDRAULICS -IE TOP IN TERMS OF

DRDNTRL

ERSATILITY AND SAFET

NSMISSION

Modular, reliable transmissions with optimum efficiency; large-capacity hydraulic pumps and powerful handlers; PTO 540 ECO as standard, and front wheel brakes for real integral braking - these are just a few of the special features of the new SAME Dorado Natural range.

Two different transmission configurations further increase the versatility of the Dorado Natural. The standard one offers 5 speeds for 3 ranges, with the shortest gear ratio enabling the tractor to move forward at a mere 298 m/h (with the engine at maximum speed); on the other hand, it can travel at 40 km/h with the engine running at just 1,800 rpm, which means significant fuel savings during fast movement on the road.

With the optional splitter (activated by means of a handy lever just beneath the steering wheel), the forward gear ratios are doubled (producing a combination of 30+15) and the shortest gear ratio enables movements of just 245 m/h (with the engine running at maximum speed). To further boost productivity levels, electrohydraulic front wheel drive and front and rear differential locking are standard.

The front axle, entirely designed and built by SAME, has a maximum steering angle of 55°, with a maximum permitted load of 2,300 kg, and the front wheels are fitted with brake discs for absolute safety.



PTO AND HYDRAULICS

The PTO comes as standard with 540 rpm and 540 ECO speed modes, but a 1,000 rpm mode or groundspeed PTO can also be added as an option. The dedicated clutch is mechanically engaged by means of a handy lever, so it's very easy to insert it gradually.

The Dorado Natural can also be successfully coupled with very demanding hydraulic equipment: the models in the range are in fact equipped with a 56 l/min pump dedicated to the rear linkage and auxiliary 4-coupler distributors (6 couplers as an option) with classic mechanical control. The steering circuit is served by an additional independent 20 I/ min pump for maximum safety and smooth driving even when the engine is at minimum speed. The rear linkage has a maximum capacity of 2,500 kg close to the ball joints, increased to 3,500 kg with the additional optional cylinders. For rear lift control is now available the EasyLift system that allows to raise and lower the implements using a single button on the console.

The ideal front loader tractor

Dorado Natural can also be pre-arranged for front loader applications thanks to the availability of Light or Ready kit directly from the factory.







DORRDO NATURAL

		70	80	90	100
INGINE					
lype			FARMo		
Emission level			Stag		
Iylinders/Displacement	n°/cc		3 / 2.		
Bore/Stroke	mm		103 /	,	
Aspiration			Turbo Int		
njection 🛛 pressure	Туре		Common Rail		
lax. power @ 2.000 rpm	kW/Hp	48,9 / 66	55,8 / 76	67 / 91	75 / 102
Rated power 🖲 2.200 rpm	kW/Hp	48 / 65	55,2 / 75	63,5 / 86	71,1 / 97
lax. torque	Nm	297 @ 1.500	341 @ 1.500	372 @ 1.400	417 @ 1.400
orque rise	%	16	28	35	35
(ISCO cooling fan		A			A
uel tank / AdBlue	1		0/-		/ 12
AT	System	DOC	+ DPF	DOC + DI	PF + SCR
RANSMISSION					
iDF transmission	Type		T33		
iearbox	п°		5 gears x	3 ranges	
TD TRANSMISSION					
huttle	Туре		Mechanical with lever	under steering wheel	
l° of speed	п°		15 +		
lax. speed	Km/h		40 ECO (@ 1.80	2 1 1	
1in. speed	m/h		29	18	
IPT TRANSMISSION WITH SPLITTER					
ihuttle	Туре		Mechanical with lever	under steering wheel	
iplitter	Туре		Mechanical, integrat	ed with shuttle lever	
° of speed	п°		30 -		
lax. speed	Km/h		40 ECO (@ 1.80	0 engine rpm)	
1in. speed	m/h		24		
то					
lechanical engagement		A	A	A	A
40/540ECO		A		A	A
40/540EC0/1000		0	0	0	0
40/540ECO + Groundspeed PTO		0	0	0	0
IFT					
lechanical rear lift		A			
lechanical rear lift with "EASYLIFT"		0	0	0	0
ear lifting capacity (STD)	Kg	2.500	2.500	2.500	2.500
ear lifting capacity (OPT)	Kg	3.500	3.500	3.500	3.500
IYDRAULICS					
ump flow (STD)	l/min	48	48	48	48
Pump flow (OPT)	l/min	56	56	56	56
lear spool valves	п°	2/3	2/3	2/3	2/3
IRAKES					
wheel braking		•			
Aechanical parking brake		A			
lydraulic Dual Mode trailer brake		0	0	0	0
WD FRONT AXLE		Ũ	Ű	Ũ	Ű
iront axle	Size	1	1	J	l
iteering angle	0	55	55	55	55
lectrohydraulic 4WD engagement					
lectrohydraulic Diff Lock engagement					
AB					
djustable steering column		A		A	A
Ipenable front and rear windows					
neumatic seat suspension		0	0	0	0
neumaric sear suspension Ianual A/C		0	0	0	0
		0	0	0	0
ligh visibility roof OPS certification				-	
UPS certification DIMENSIONS		0	0	0	0
	c:	"סבם סקי סבו	"סכם סד/ סכן/	"סבם סקי סבו/	"סרם ס <i>דו</i> חבו/
Vith rear tyre	Size	420/70 R30"	420/70 R30"	420/70 R30"	420/70 R30"
/heelbase	mm	001.5	2.100	001.5	2.100
lax. length	mm	3.890	3.890	3.890	3.890
entre rear axle – Cab	mm	1.820	1.820	1.820	1.820
iotal height	mm	2.520	2.520	2.520	2.520
Vidth	mm	1.882	1.882	1.882	1.882
Veight	Kg	3.250	3.250	3.350	3.350
otal admissible load	Kg	5.200	5.200	5.200	5.200
STD OPT Not available					

TECHNICAL DATA

÷

÷

1

1

1

